

0.6
11/2/20
hu
a single substrate body defined by an upper surface and formed with at least one cavity including an upper cavity formed on the upper surface of the substrate body and a primary optical path for accommodating the passage of a light beam aligned in a predetermined orientation with the upper cavity;

a beam steering assembly having a steerable element positioned substantially adjacent the upper cavity for controllably directing the light beam;

a hinge for flexibly connecting the beam steering assembly with an upper edge of the upper cavity that is not coincident with the primary optical path;

wherein the beam steering assembly includes at least one reflective surface such that the beam steering assembly is disposed within the upper cavity so that an impinging beam of light emanating from the primary optical path is controllably deflected in the same general direction the upper cavity is facing and wherein a beam of light entering from the same general direction the upper cavity is facing is controllably deflected towards said primary optical path.

70. (Not amended) An optical head assembly comprising:

a single substrate body defined by an upper surface and formed with at least one cavity including an upper cavity formed on the upper surface of the substrate body and a primary optical path for accommodating the passage of a light beam aligned in a predetermined orientation with the upper cavity; and

A
a beam steering assembly rigidly affixed in a predetermined orientation within at least a portion of the upper cavity having a steerable element positioned substantially adjacent the upper cavity for controllably directing the light beam through at least a portion of the upper cavity.